




REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



NOTES

- 1 . MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT
ROD - HARDENED STEEL BLACK NITRIDE
- 2 . FORCE :90LBS/400.5N
- 3 . DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
- 4 . DRAWING LENGTHS (NOT DIMENSIONED) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
- 5 . OPERATING TEMPERATURE : - 30 C TO + 80 C
- 6 . Label to include part number , date code , and warning message Label not to be remove
- 7 . Gas Spring not to be modified , or changed from manufactured , original , product
- 8 . Gas Spring to is suggested to be mounted shaft down (rod down) for maximum performance
- 9 . Connectors to be lined up per drawing . 5 degree deviation permitted
- 10 . Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - objects
- 11 . Gas Spring to be assembled per the drawing with end fittings assembled / fastened
- 12 . Gas Springs are not to be opened
- 13 . Inside of each end fitting to be greased

	DRAWN	NAME	DATE
	CHECKED	Allen	12/13/19
<small>THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NORMONT. THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORIZATION IS STRICTLY FORBIDDEN.</small>	DWG NO		REV
	NSG1200M90MT1		0
	TITLE		
Gas Spring			
<small>REMOVE ALL BURRS & BREAK ALL SHARP EDGES</small>	TOLERANCES		<small>THIRD ANGLE PROJECTION</small>  <small>SHEET 1 OF 1</small>
	X.X	±0.060	
	X.XX	±0.030	
	X.XXX	±0.015	
ALL DIMENSIONS ARE IN		SCALE	
inch		N.T.S	
UNLESS OTHERWISE SPECIFIED		SIZE	B
ANGLES ±1.0°			
HOLES ±0.005			