


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



**NOTES**

1. MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT  
ROD - HARDENED STEEL BLACK NITRIDE
2. FORCE: 120LBS/ 534N
3. DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
4. DRAWING LENGTHS ( NOT DIMENSIONED ) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
5. OPERATING TEMPERATURE : - 3 0 C TO + 8 0 C
6. Label to include part number , date code , and warning message Label not to be remove
7. Gas Spring not to be modified , or changed from manufactured , original , product
8. Gas Spring to is suggested to be mounted shaft down ( rod down ) for maximum performance
9. Connectors to be lined up per drawing . 5 degree deviation permitted
10. Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - objects
11. Gas Spring to be assembled per the drawing with end fittings assembled / fastened
12. Gas Springs are not to be opened
13. Inside of each end fitting to be greased



THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NUCMENG. THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.

REMOVE ALL  
BURRS & BREAK  
ALL SHARP  
EDGES

ALL DIMENSIONS ARE IN  
**inch**  
UNLESS OTHERWISE SPECIFIED

	NAME	DATE
DRAWN	Allen	12/13/19
CHECKED		
DWG NO	NSG1221M120PC1	REV 0
TITLE <b>Gas Spring</b>		
TOLERANCES	THIRD ANGLE PROJECTION	SCALE
X.X ±0.060		N.T.S.
X.XX ±0.030		SIZE
X.XXX ±0.015		B
ANGLES ±1.0°		
HOLES ±0.005	SHEET 1 OF 1	