


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



- NOTES**
1. MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT  
ROD - HARDENED STEEL BLACK NITRIDE
  2. FORCE :150LBS/667.5N
  3. DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
  4. DRAWING LENGTHS ( NOT DIMENSIONED ) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
  5. OPERATING TEMPERATURE : - 30 C TO + 80 C
  6. Label to include part number , date code , and warning message Label not to be remove
  7. Gas Spring not to be modified , or changed from manufactured , original , product
  8. Gas Spring to is suggested to be mounted shaft down ( rod down ) for maximum performance
  9. Connectors to be lined up per drawing . 5 degree deviation permitted
  10. Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - obiects
  11. Gas Spring to be assembled per the drawing with end fittings assembled / fastened
  12. Gas Springs are not to be opened
  13. Inside of each end fitting to be greased



THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NUOMENG  
THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.

REMOVE ALL BURRS & BREAK ALL SHARP EDGES

ALL DIMENSIONS ARE IN **inch** UNLESS OTHERWISE SPECIFIED

DRAWN	NAME Allen	DATE 12/13/19
CHECKED		
DWG NO NSG1700M150MT1		REV 0
TITLE <b>Gas Spring</b>		
TOLERANCES	THIRD ANGLE PROJECTION	SCALE N.T.S.
X.X ±0.060		SIZE B
X.XX ±0.030		
X.XXX ±0.015		
ANGLES ±1.0°		
HOLES ±0.005	SHEET 1 OF 1	