




REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



- NOTES
1. MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT
ROD - HARDENED STEEL BLACK NITRIDE
 2. FORCE: 40LBS/ 178N
 3. DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
 4. DRAWING LENGTHS (NOT DIMENSIONED) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
 5. OPERATING TEMPERATURE : - 3 0 C TO + 8 0 C
 6. Label to include part number , date code , and warning message Label not to be remove
 7. Gas Spring not to be modified , or changed from manufactured , original , product
 8. Gas Spring to is suggested to be mounted shaft down (rod down) for maximum performance
 9. Connectors to be lined up per drawing . 5 degree deviation permitted
 10. Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - objects
 11. Gas Spring to be assembled per the drawing with end fittings assembled / fastened
 12. Gas Springs are not to be opened
 13. Inside of each end fitting to be greased

	NAME	DATE
	Allen	12/13/19
<small>THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NORMONT. THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.</small>	DWG NO	REV
	NSG1963M40PC1	0
<small>REMOVE ALL BURRS & BREAK ALL SHARP EDGES</small>	TITLE	SCALE
	Gas Spring	N.T.S.
<small>ALL DIMENSIONS ARE IN inch UNLESS OTHERWISE SPECIFIED</small>	TOLERANCES	THIRD ANGLE PROJECTION
	XX ±0.060 XXX ±0.030 XXXX ±0.015 ANGLES ±1.0° HOLES ±0.005	 SHEET 1 OF 1
SIZE	B	